



**WACKER  
NEUSON**  
*all it takes!*

## PS2-1500

### Submersible Pump

Heavy-duty and durable for demanding dewatering tasks

No matter how large or small the job, Wacker Neuson's single-phase submersible pumps offer the versatility and durability contractors need for light dewatering on the job site.

### Highlights

- Variety of models
- Reliable protection against water creepage
- Perfect sealing of the engine compartment by double, internally placed mechanical seal made of silicon carbide in the oil bath
- Oil lifter for reliable lubrication in any situation
- Safe to run dry
- Steel sleeve reduces wear of the shaft

### Technical Data

#### ■ Electrical - Output Details

Nominal current	15.40 A
Nominal voltage	230.0 V
Nominal frequency	50.0 Hz
Phase	1.0 ~

#### ■ Mechanical - Output Details

Flow rate max.	440.0 l/min
Solid diameter max.	6.0 mm
Delivery height max.	17.5 m

#### ■ Mechanical Details

Length	187.0 mm
--------	----------

Width	187.0 mm
Height	600.0 mm
Operating weight	33.0 kg
Intake-/Pressure socket-dia.	50.0 mm

#### ■ Motor

Nominal speed	2,900.0 1/min
---------------	---------------

#### ■ Electrical System

Length Cable	10.0 m
Cable cross-section	4.0 mm <sup>2</sup>