



IRSE-FU45/230 Laser

High-frequency internal vibrators

Concrete consolidation with comfortable operation

The Wacker Neuson IRSE-FU high-frequency internal vibrators have a short protection hose and low vibration handle. The ergonomically designed handle with vibration damping offers a high degree of comfort during operation. Wacker Neuson's IRSEN models/IRSE-FU models of high-quality internal vibrators offer a variety of features and benefits.

Highlights

- Bodyguard
- Handle (Low Vib)
- High-performance electric motor with stable speeds
- Switch box with integrated frequency converter

Technical Data

■ Electrical - Output Details	
Nominal current	4.80 A
Nominal voltage	220.0 - 240.0 V
Nominal frequency	50.0 - 60.0 Hz
Nominal power [P]	0.88 KW
Phase	1.0 ~
Mechanical - Output Details	
Amplitude at air	2.300 mm
Vibrations	12,000.0 1/min
Vibrations (Hz)	200.0 Hz
Mechanical Details	
Length Hose	0.3 m

Weight	14.50 kg
Rubber cap	no
Motor	
Motor type	Asynchronous motor
Environment Data	
Protection class	I / Protective earthing
Degree of protection	IP67
Electrical System	
•	
Breaker Switch On/Off	Yes
Breaker Switch On/Off Integrated transformer	Yes yes

The illustrations, equipment and data shown may deviate from the current delivery program of your country. Optional equipment subject to additional charge may be shown. Subject to changes